

Configuration	Standard	Roller Suspension Option
Engine		
Emissions Tier (EPA)	Tier 4	Tier 4
Engine Cooling	Liquid	
Engine Fuel	Diesel	
Horsepower	66 hp	
Turbocharged Engine	<input checked="" type="checkbox"/>	
Performance		
Rated Operating Capacity (SAE)	2000 lb	2100 lb
Operating Capacity (50% of Tip)	2857 lb	3000 lb
Tipping Load	5714 lb	6000 lb
Operating Weight	8393 lb	7948 lb
Travel Speed	7.3 mph	7.3 mph
Ground Pressure (Rubber)	6 psi	5.7 psi
Capacities		
Fuel Tank	24.8 gal	24.8 gal
Hydraulic System		
System Relief @ Quick Couplers	3500 psi	
Auxiliary Std Flow	17.1 gal/min	
Auxiliary High Flow	26.7 gal/min	
Dimension		
Length	133 in	
Length without Attachment	104.6 in	
Length with Standard Bucket	133 in	
Width	71.5 in	67.1 in
Width (with bucket)	74 in	68 in
Height	77.8 in	
Height with Operator Cab	77.8 in	
Height to Bucket Hinge Pin	119 in	
Reach @ Maximum Height	34.9 in	
Turning Radius	80 in	80 in
Length of track on ground	55.2 in	
Track Width	12.6 in	
Track Width - Optional	15.8 in	
Features		
Joystick Control	<input checked="" type="checkbox"/>	
Air Conditioning	<input checked="" type="checkbox"/>	
Backup Alarm	<input type="checkbox"/>	
BICS System (Interlock)	<input type="checkbox"/>	
Cab Heater	<input checked="" type="checkbox"/>	
Operating Lights	<input type="checkbox"/>	
Suspension Seat	<input type="checkbox"/>	
Two Speed Travel	N/A	
Deluxe Instrumentation	<input checked="" type="checkbox"/>	
Engine Shutdown	<input type="checkbox"/>	
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>	
High Flow Option	<input checked="" type="checkbox"/>	
Auxiliary Hydraulics	<input type="checkbox"/>	
Bob-Tach Attachment System	<input type="checkbox"/>	
Power Bob-Tach	<input checked="" type="checkbox"/>	
ACS (Switchable Controls)	<input checked="" type="checkbox"/>	
Ride Control	<input checked="" type="checkbox"/>	
Horn	<input type="checkbox"/>	